



## Datasheet for: WM7529

### Product Type: Enclosed isolating transformers

7500VA 230v to 120v Hardwired



VA	7500
Input Voltage	230
Input Termination	3 x M6 Studs
Input Current	33
amps	62.5
Output Voltage	120
Output Termination	Terminal Posts
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	Ht:454 L: 384 W:305 (mm)
Weight	45kg
Primary Protection	MCB 2P 40amp type C
Surge Protection	MS35 50A Surge Limiter
Product Type	Safety Isolating transformer Conforms to EN61558-2-06 CE & RoHS
Regulation	0.02

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product WM7529 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
03/06/2026



www.airlinktransformers.com - VAT No. 573 1888 10  
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478  
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS  
01279 431865 | sales@airlinktransformers.com