



Datasheet for: SD1544

Product Type: Low voltage portable Tool transformers

750VA 110v to 2 x 24v site transformer with sockets

VA	750
Input Voltage	110
Input Termination	Mains lead with Yellow 16amp plug
Input Current	6.8
amps	32
Output Voltage	24
Output Notes	750VA continuous rating (2 x 16A)
Output Termination	Two 16amp Purple 3P sockets
Product Case	601 Tough GRP case with carrying handle IP44
Dimension	Ht:210 W:165 D:165
Weight	8kg
Primary Protection	Push to reset circuit breaker SP8
Surge Protection	SL15 Surge Limiter
Product Type	Safety Isolating transformer
Standard	Conforms to EN61558-2-06 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product SD1544 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
23/06/2026


