

Datasheet for: SV1042

Product Type: Low voltage portable Tool transformers

500VA 110v to 42v Site Transformer with Socket



VA	500
Input Voltage	110
Input Termination	2M Mains lead with Yellow 16amp Plug
Input Current	4.5
amps	12
Output Voltage	42
Output Notes	500va continuous rating
Output Termination	Single 16amp Purple Socket
Product Case	601 Tought GRP case with carrying handle IP44
Dimension	Ht:210 W:165 D:165
Weight	6kg
Primary Protection	Push to reset circuit breaker SP3
Surge Protection	SL15 Surge Limitor
Product Type	Safety Isolating transformer
Standard	Conforms to EN61558-2-06 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

07/02/2023


