

# Datasheet for: Model 3 Type 2 small

## Product Type: Electric Vehicle Transformers

New charging box for electric car. Small, simple and safe-of course in accordance with all European requirements. The only setting is the choice of charging current (6-18A), which the electric installer sets when mounting. The user connects and disconnects as needed, no lock. Only a simple and easy to understand lamp for the status of charging



VA	4200
Input Voltage	230
Output Voltage	230
Dimension	120x200x105mm
Weight	1kg
Primary Protection	Only needs single combination protection type A in
Secondary Protection	Has built in Earth fault sensor (RCD-DC) for DC po
Standard	CE compliance with NEK IEC 61851-1 (2017) and EU Di
Notes	10 position rotation switch for setting the charging current from 6 to 18 A in the following steps: 6, 7, 8, 9, 10, 13, 14, 15, 16, 18 Only single phase Type 2 contact in advance. No motor lock. Ihht: NEK400:2018 Point 722.531.3.101
Fixing	Easy to assemble with cable glands in the bottom

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.

02/04/2023


