



Datasheet for: EL0152W

Product Type: Outdoor Waterproof Transformers

150VA 230v to Single 24v

VA	150
Input Voltage	230
Input Termination	500mm White mains lead 2 core 1mm
Input Current	0.6521739130434783
amps	6.25
Output Voltage	24
Output Termination	2 meter Black mains lead 2 core 2.5mm
Product Case	108 Black plastic case IP68
Dimension	Ht:70 Od:108 (mm)
Weight	1.95kg
Primary Protection	MO3 Self resetting Thermal-current cutout
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Notes	Housed in a durable waterproof case

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
26/10/2020

