

Datasheet for: EL0252W

Product Type: Outdoor Waterproof Transformers

250VA 230v to Single 24v

| | |
|--------------------|---|
| VA | 250 |
| Input Voltage | 230 |
| Input Termination | 500mm White mains lead 2 core 1mm |
| Input Current | 1.08695652173913 |
| amps | 10.4166666666667 |
| Output Voltage | 24 |
| Output Termination | 2 meter Black mains lead 2 core 2.5mm |
| Product Case | 130 Black plastic case IP68 |
| Dimension | Ht:70 Od:130 (mm) |
| Weight | 2.1kg |
| Primary Protection | MO3 Self resetting Thermal-current cutout |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Notes | Housed in a durable waterproof case |



Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
17/05/2022




www.airlinktransformers.com - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5TF
01279 431865 | sales@airlinktransformers.com