

Datasheet for: EL0324W

Product Type: Outdoor Waterproof Transformers

300VA 230v to Single 24v



| | |
|--------------------|---|
| VA | 300 |
| Input Voltage | 230 |
| Input Termination | 500mm White mains lead 2 core 1mm |
| Input Current | 1.304347826086957 |
| amps | 12.5 |
| Output Voltage | 24 |
| Output Termination | 2 meter Black mains lead 2 core 4mm |
| Product Case | 130 Black plastic case IP68 |
| Dimension | Ht:70 Od:130 (mm) |
| Weight | 2.1kg |
| Primary Protection | MO3 Self resetting Thermal-current cutout |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Notes | Housed in a durable waterproof case |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
23/09/2019



R. Harris

