



## Datasheet for: WP0050

### Product Type: Outdoor Waterproof Transformers

50VA 230v to Single 12v Waterproof transformer

VA	50
Input Voltage	230
Input Termination	TB1 2way screw terminal Small 15Amp
Input Current	0.2173913043478261
amps	4.16666666666667
Output Voltage	12
Output Termination	TB1 2way screw terminal Small 15Amp
Product Case	WP2 Small durable grey plastic case Waterproof to IP56 (Free standing)
Dimension	Ht:50 L:100 W:100 (mm)
Weight	2kg
Primary Protection	MO3 Self resetting Thermal-current cutout
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Notes	Fitted with two waterproof glands

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product WP0050 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 06/07/2026



