



## Datasheet for: WP0052

### Product Type: Outdoor Waterproof Transformers

50VA 230v to Single 24v Waterproof transformer

|                    |  |
|--------------------|--|
| VA                 | 50   |
| Input Voltage      | 230  |
| Input Termination  | TB1 2way screw terminal Small 15Amp                                    |
| Input Current      | 0.2173913043478261   |
| amps               | 2.08333333333333   |
| Output Voltage     | 24   |
| Output Termination | TB1 2way screw terminal Small 15Amp                                    |
| Product Case       | WP2 Small durable grey plastic case Waterproof to IP56 (Free standing) |
| Dimension          | Ht:70 L:100 W:100 (mm)   |
| Weight             | 2kg  |
| Primary Protection | MO3 Self resetting Thermal-current cutout                              |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS        |
| Notes              | Fitted with two waterproof glands                                      |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product WP0052 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
14/02/2026

