

**Datasheet for: WP0250** 

**Product Type: Outdoor Waterproof** 

**Transformers** 

250VA 230v to Single 12v Waterproof transformer

VA 250 Input Voltage 230

Input Termination TB03 2way screw terminal Medium 24A

Input Current 1.08695652173913 amps 20.833333333333

Output Voltage 12

Output Termination TB03 2way screw terminal Medium 24A

Product Case 601 Black Durable reinforced waterproof case IP67

Dimension Ht:185 W:160 L:160

Weight 3.5kg

Primary Protection MO3 Self resetting Thermal-current cutout

Surge Protection SL15 Surge Limitor

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Notes Two waterproof glands supplied loose

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product WP0250 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 25/11/2025

