



Datasheet for: WP1524

Product Type: Outdoor Waterproof Transformers

1500VA 230v to Single 24v Waterproof transformer

VA	1500
Input Voltage	230
Input Termination	TB04 2way screw terminal Large 76A
Input Current	6.521739130434782
amps	62.5
Output Voltage	24
Output Termination	TB04 2way screw terminal Large 76A
Product Case	701 Black Durable reinforced waterproof case IP67
Dimension	Ht:260 W:190 L:190
Weight	11kg
Primary Protection	SP10 Push to reset circuit breaker
Surge Protection	SL32 Surge Limitor
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Notes	Two waterproof glands supplied loose

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product WP1524 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
16/06/2026



