



Datasheet for: WP3024

Product Type: Outdoor Waterproof Transformers

3000VA 230v to Single 24v Waterproof transformer

VA	3000
Input Voltage	230
Input Termination	TB04 3way screw terminal Large 76A
Input Current	13
amps	125
Output Voltage	24
Output Termination	M6 studs
Product Case	801 Yellow Durable reinforced waterproof case IP67
Dimension	Ht:380 W:290 L:320
Weight	22kg
Primary Protection	SP6 Push to reset circuit breaker
Surge Protection	SL32 Surge Limiter
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Notes	Two waterproof glands supplied loose

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
22/09/2019

