

Datasheet for: BPS7500MP

Product Type: Standard Balanced Power Supply

7500VA Multi primary 230-240-250V to 230v CTE MCB & RCBO
Hardwired



VA	7500
Input Voltage	230
Input Termination	Screw terminals
Input Current	32
amps	32
Output Voltage	230 CTE
Output Notes	The BPS7500MP has an adjustable input voltage of 230/240/250V and a 230V balanced output giving the facility to raise or lower the output voltage. Especially popular in high voltage areas.
Output Termination	Screw terminals
Product Case	P5 Industrial floor/wall mounting case IP23
Dimension	H:454, L:384, W:305 mm
Weight	45kg
Primary Protection	MCB'S 32A 2P+N Type C
Secondary Protection	RCBO 32A 2P Type C
Surge Protection	MS35 Surge Limiter
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product BPS7500MP conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
15/12/2025

