

Datasheet for: CM0050222

Product Type: Standard Range Toroidal Transformers

50VA 230v to 2x22v



| | |
|--------------------|---|
| VA | 50 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 16/.2 |
| Input Current | 0.217 |
| amps | 1.14 |
| Output Voltage | 22+22 |
| Output Termination | 200mm Flexible leads 24/.2 |
| Dimension | OD: 80 Ht: 38mm |
| Weight | 0.75kg |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.14 |
| Fixing | Hardware 2x 50mm Neoprene pads + steel dish washer with bolt |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM0050222 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
16/09/2025

