

Datasheet for: CM0050230

Product Type: Standard Range Toroidal Transformers

50VA 230v to 2x30v



VA	50
Input Voltage	230
Input Termination	200mm Flexible leads 16/.2
Input Current	0.217
amps	0.83
Output Voltage	30+30
Output Termination	200mm Flexible leads 24/.2
Dimension	OD: 80 Ht: 38mm
Weight	0.75kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.14
Fixing	Hardware 2x 50mm Neoprene pads + steel dish washer with bolt

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM0050230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
16/09/2025

