

Datasheet for: CM0050250

**Product Type: Standard Range Toroidal** 

**Transformers** 

50VA 230v to 2x50v

VA 50 Input Voltage 230

Input Termination 200mm Flexible leads 16/.2

Input Current 0.217 amps 0.5 Output Voltage 50+50

Output Termination 200mm Flexible leads 24/.2

Dimension OD: 80 Ht: 38mm

Weight 0.75kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.14

Fixing Hardware 2x 50mm Neoprene pads + steel dish washer with bolt

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM0050250 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105deqC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 16/09/2025

