

## Datasheet for: CM0150223

### Product Type: Standard Range Toroidal Transformers

150VA 230V to 2x23V Chassis Mount Transformer



VA	150
Input Voltage	230
Input Termination	200mm Flexible leads 18awg
Input Current	0.65
amps	6.5
Output Voltage	23+23
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 90 Ht: 55mm
Weight	1.5kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.1
Fixing	Hardware 2x90mm Neoprene pads + steel dish washer with bolt

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product CM0150223 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
16/09/2025

A handwritten signature in black ink.