

Datasheet for: CM0500214

Product Type: Standard Range Toroidal Transformers

500VA 230v to 2x14v



| | |
|--------------------|--|
| VA | 500 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 16awg |
| Input Current | 2.17 |
| amps | 17.85 |
| Output Voltage | 14+14 |
| Output Termination | 200mm Flexible leads 14awg |
| Dimension | OD: 140 Ht: 60mm |
| Weight | 4.2kg |
| Product Type | Safety Isolating transformer |
| Standard | Conforms to EN61558-2-06 CE & RoHS |
| Regulation | 0.05 |
| Fixing | Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 70mm |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM0500214 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
15/04/2026

