



Datasheet for: CM0625226

Product Type: Standard Range Toroidal Transformers

625VA 230v to 2x26v

| | |
|--------------------|--|
| VA | 625 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 16awg |
| Input Current | 2.7 |
| amps | 12 |
| Output Voltage | 26+26 |
| Output Termination | 200mm Flexible leads 16awg |
| Dimension | OD: 140 Ht: 70mm |
| Weight | 5kg |
| Product Type | Safety Isolating transformer |
| Standard | Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.05 |
| Fixing | Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 75mm |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM0625226 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 22/12/2024

