

Datasheet for: CM0625226

**Product Type: Standard Range Toroidal** 

**Transformers** 

625VA 230v to 2x26v

VA 625 Input Voltage 230

Input Termination 200mm Flexible leads 16awg

Input Current 2.7
amps 12
Output Voltage 26+26

Output Termination 200mm Flexible leads 16awg

Dimension OD: 140 Ht: 70mm

Weight 5kg

Product Type Safety Isolating transformer

Standard Conforms to EN61558-2-23 CE & RoHS

Regulation 0.05

Fixing Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 75mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM0625226 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

17/07/2025





www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com