

Datasheet for: CM0750424

Product Type: Standard Range Toroidal

Transformers

750VA 230v to 4x24v

VA 750 Input Voltage 230

Input Termination 200mm Flexible leads 16awg

3.2 Input Current 7.8 amps Output Voltage 4 X 24

Output Termination 200mm Flexible leads 16awg

Dimension OD: 140 Ht: 75mm

Weight 5.5kg

Product Type Safety Isolating transformer

Standard Conforms to EN61558-2-6 CE & RoHS

Regulation

Fixing Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 75mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM0750424 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.



