

## Datasheet for: CM1500415

### Product Type: Standard Range Toroidal Transformers

1500VA 230V to 4x15V



|                    |   |
|--------------------|---|
| VA                 | 1500  |
| Input Voltage      | 230   |
| Input Termination  | 200mm Flexible leads 16awg  |
| Input Current      | 6.5   |
| amps               | 25  |
| Output Voltage     | 15+15+15+15   |
| Output Termination | 200mm Flexible leads 16awg  |
| Dimension          | OD: 175 Ht: 85mm  |
| Weight             | 10kg  |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS       |
| Regulation         | 0.04  |
| Fixing             | Hardware 2x135mm Neoprene pads + steel dish washer with bolt M8 100mm |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM1500415 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
02/04/2025



