

Datasheet for: CM2500174

Product Type: Standard Range Toroidal Transformers

2500VA 100V to 230V



VA	2500
Input Voltage	100
Input Termination	200mm Flexible leads 14awg
Input Current	25
amps	10.9
Output Voltage	230
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 205 Ht: 85mm
Weight	14kg
Product Type	Safety Isolating transformer
Standard	Conforms to EN61558-2-06 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 10mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM2500174 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
16/09/2025



www.airlinktransformers.com - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com