

**Datasheet for: CM3000236**

**Product Type: Standard Range Toroidal Transformers**

3000VA 230V to 2x36V



VA	3000
Input Voltage	230
Input Termination	200mm Flexible leads 14awg
Input Current	13
amps	41
Output Voltage	36+36
Output Termination	200mm Flexible leads 12awg
Dimension	OD: 205 Ht: 110mm
Weight	17kg
Product Type	Safety Isolating Transformer
Standard	Conforms to EN61558-2-6 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 12mm

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethern Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM3000236 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
23/02/2025

