Datasheet for: CM3000236

Product Type: Standard Range Toroidal Transformers

3000VA 230V to 2x36V



VA	3000
Input Voltage	230
Input Termination	200mm Flexible leads 14awg
Input Current	13
amps	41
Output Voltage	36+36
Output Termination	200mm Flexible leads 12awg
Dimension	OD: 205 Ht: 110mm
Weight	17kg
Product Type	Safety Isolating Transformer
Standard	Conforms to EN61558-2-6 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 12mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM3000236 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
03/11/2026

www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com