

Datasheet for: CM3300255

Product Type: Standard Range Toroidal

Transformers

3300VA 230v to 2x55v

VA 3300 Input Voltage 230

Input Termination 200mm Flexible leads 16awg

Input Current 14.35 amps 30 Output Voltage 55 + 55

Output Notes Outputs may be wired in series to give 110V CTE

Output Termination 200mm Flexible leads 16awg

Dimension OD: 205 Ht: 110mm

Weight 17kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.03

Fixing Potted centre Drilled 10mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM3300255 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105deqC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

13/12/2025

