



Datasheet for: CM4000179

Product Type: Standard Range Toroidal Transformers

4000VA 120V to230V

VA	4000
Input Voltage	120
Input Termination	200mm Flexible leads 12awg
Input Current	33.3
amps	13
Output Voltage	230
Output Termination	200mm Flexible leads 14awg
Dimension	OD: 240 Ht: 100mm
Weight	26kg
Product Type	Safety Isolating transformer
Standard	Conforms to EN61558-2-06 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 10mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM4000179 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
14/06/2026



[Handwritten signature]

