

**Datasheet for: CM5000174**

**Product Type: Standard Range Toroidal Transformers**

5000VA 100V to 230V



|                    |                                    |
|--------------------|------------------------------------|
| VA                 | 5000                               |
| Input Voltage      | 100                                |
| Input Termination  | 200mm Flexible leads 10awg         |
| Input Current      | 50                                 |
| amps               | 21.7                               |
| Output Voltage     | 230                                |
| Output Termination | 200mm Flexible leads 14awg         |
| Dimension          | OD: 240 Ht: 110mm                  |
| Weight             | 22kg                               |
| Product Type       | Safety Isolating transformer       |
| Standard           | Conforms to EN61558-2-06 CE & RoHS |
| Regulation         | 0.03                               |
| Fixing             | Fixing Potted centre Drilled 10mm  |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM5000174 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
02/04/2025

