# Datasheet for: CM5000174

## Product Type: Standard Range Toroidal Transformers

5000VA 100V to 230V



| | |
|---|---|
| VA | 5000 |
| Input Voltage | 100 |
| Input Termination | 200mm Flexible leads 10awg |
| Input Current | 50 |
| amps | 21.7 |
| Output Voltage | 230 |
| Output Termination | 200mm Flexible leads 14awg |
| Dimension | OD: 240 Ht: 110mm |
| Weight | 22kg |
| Product Type | Safety Isolating transformer |
| Standard | Conforms to EN61558-2-06 CE & RoHS |
| Regulation | 0.03 |
| Fixing | Fixing Potted centre Drilled 10mm |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM5000174 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.
23/11/2026

www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com