



## Datasheet for: CM5000178

### Product Type: Standard Range Toroidal Transformers

5000VA 400v to 110v

VA	5000
Input Voltage	400
Input Termination	200mm Flexible leads 14awg
Input Current	12.5
amps	45.45
Output Voltage	110
Output Termination	200mm Flexible leads 10awg
Dimension	OD: 240 Ht: 110mm
Weight	22kg
Product Type	Safety Isolating transformer
Standard	Conforms to EN61558-2-6 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 10mm

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product CM5000178 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
04/07/2026



www.airlinktransformers.com - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478  
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS  
01279 431865 | sales@airlinktransformers.com