



**Datasheet for: CM5000255**

**Product Type: Standard Range Toroidal Transformers**

5000VA 230v to 2x55v

VA	5000
Input Voltage	230
Input Termination	200mm Flexible leads 14awg
Input Current	21.7
amps	45.5
Output Voltage	55+55
Output Termination	200mm Flexible leads 12awg
Dimension	OD: 240 Ht: 110mm
Weight	27kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 12mm

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM5000255 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 04/07/2026



*[Handwritten signature]*

