



Datasheet for: CM6000290

Product Type: Standard Range Toroidal Transformers

6000VA 230V to 2 x 90V

| | |
|--------------------|-----------------------------------------------------------------|
| VA | 6000 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 12awg |
| Input Current | 26 |
| amps | 66 |
| Output Voltage | 90 + 90 |
| Output Notes | 2 x 90V @ 33A |
| Output Termination | 200mm Flexible leads 12awg |
| Dimension | OD: 240 Ht: 120mm |
| Weight | 31kg |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.03 |
| Fixing | Potted & Centre Drilled 12mm |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethern Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM6000290 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
15/04/2026

