

Datasheet for: CM6000290

Product Type: Standard Range Toroidal

Transformers

6000VA 230V to 2 x 90V

VA 6000 Input Voltage 230

Input Termination 200mm Flexible leads 12awg

 Input Current
 26

 amps
 66

 Output Voltage
 90 + 90

 Output Notes
 2 x 90V @ 33A

Output Notes 2 x 90 v @ 33A

Output Termination 200mm Flexible leads 12awg

Dimension OD: 240 Ht: 120mm

Weight 31kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.03

Fixing Potted & Centre Drilled 12mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM6000290 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

16/09/2025

