



**Datasheet for: CM75001230**

**Product Type: Standard Range Toroidal Transformers**

7500VA 230V to 230V

|                    |  |
|--------------------|--|
| VA                 | 7500   |
| Input Voltage      | 230  |
| Input Termination  | 200mm Flexible leads 12awg                         |
| Input Current      | 32   |
| amps               | 32   |
| Output Voltage     | 230  |
| Output Termination | 200mm Flexible leads 12awg                         |
| Dimension          | OD: 270 Ht: 135mm                                  |
| Weight             | 34kg   |
| Standard           | Safety Isolating transformer Conforms to EN61558-2 |
| Regulation         | 0.03   |
| Fixing             | Potted & Centre Drilled 12mm                       |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM75001230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 05/05/2026

