



**Datasheet for: CM75001230**

**Product Type: Standard Range Toroidal Transformers**

7500VA 230V to 230V

VA	7500
Input Voltage	230
Input Termination	200mm Flexible leads 12awg
Input Current	32
amps	32
Output Voltage	230
Output Termination	200mm Flexible leads 12awg
Dimension	OD: 270 Ht: 135mm
Weight	34kg
Standard	Safety Isolating transformer Conforms to EN61558-2
Regulation	0.03
Fixing	Potted & Centre Drilled 12mm

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM75001230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 14/06/2026



*[Handwritten signature]*

