

Datasheet for: UK-US5120NEMA

Product Type: Use American Appliances in The UK

5000VA 230V to 240V (2x120V) with Nema 14-30R Output Connector



| | |
|----------------------|---|
| VA | 5000 |
| Input Voltage | 230 |
| Input Termination | Screw terminals |
| Input Current | 22 |
| amps | 50 |
| Output Voltage | 240 |
| Output Notes | Supplies 2 x 120V out of phase via Nema 14-30R connector to give total 240V for large US appliances. Optional L14-30R socket available. |
| Output Termination | Nema 14-30R US Large Appliance Connector |
| Product Case | P5 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:353 L: 350 W:242 (mm) |
| Weight | 35kg |
| Primary Protection | MCB 25A 2P |
| Secondary Protection | 2 x 32A MCB |
| Surge Protection | MS35 Surge Limiter |
| Product Type | Safety Isolating transformer |
| Standard | Conforms to EN61558-2-6 CE & RoHS |
| Notes | Available in hard wired format for installation in RV etc. |
| Fixing | Floor/Wall mount |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product UK-US5120NEMA conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
10/09/2025


